

**Hartmetall-Werkzeugfabrik Paul Horn GmbH****MSDS Safety Information****Product: Cemented Carbide MG 12**

MSDS Date: 20/06/2001

MSDS Num: 0002

Product ID: CEMENTED CARBIDE MG 12

MFN: 01

Responsible Party

Cage:

Name: Paul Horn GmbH

Address: Unter dem Holz 33-35

City: D-72072 Tübingen

Info Phone Number: 0049-7071-7004-0

Emergency Phone Number:

Review Ind: Y

Published: Y

Preparer Co. when other than Responsible Party Co.

Cage:

Name: Hartmetall-Werkzeugfabrik Paul Horn GmbH

Address: Unter dem Holz 33-35

City: D-72072 Tübingen

Contractor Summary

Cage:

Name: Hartmetall-Werkzeugfabrik Paul Horn GmbH

Address: Unter dem Holz 33-35

City: D-72072 Tübingen

Phone: 0049-7071-7004-0

Ingredients

Cas: 7440-48-4

RTECS #: GF8750000

Name: COBALT (ANIMAL CARCINOGEN BY IARC - GROUP 2B)

% Wt: 0-13

Other REC Limits: 0.05 PPM

OSHA PEL: 0.1 MG/CUM

ACGIH TLV: 0.05 MG/CUM

Cas: 12070-06-3

RTECS #: 1002631TC

Name: TANTALUM CARBIDE

% Wt: 0-50

OSHA PEL: 5 MG/CUM

ACGIH TLV: 5 MG/CUM

Cas: 7440-62-2

RTECS #: N/A

Name: VANADIC CARBIDE

% Wt: N/A



Cas: 12069-94-2
RTECS #: 1002633NC
Name: NIOBIUM CARBIDE
% Wt: 0-8

Cas: 12070-12-1
RTECS #: YO7250000
Name: TUNGSTEN CARBIDE
% Wt: 5-94
Other REC Limits: 5 MG(W)/M3
ACGIH TLV: 5 MG(W)/M3

=====
Health Hazards Data
=====

Route Of Entry Inds - Inhalation: YES
Skin: YES
Ingestion: YES
Carcinogenicity Inds - NTP: YES
IARC: YES
OSHA: NO

Effects of Exposure: GRINDING CEMENTED MAY PRODUCE POTENTIALLY HAZARDOUS DUST WHICH CAN BE INHALED, SWALLOWED, COME IN CONTACT W/SKIN & EYES. INHALATION: NOSE & THROAT IRRITATION. POTENTIAL FOR TRANSIENT RESPIRATORY REACTION IN COBALT HYPERSENSITIZED INDIVIDUAL S. PROLONGED USE: PERMANENT/FATAL RESPIRATORY DISEASES. (SEE SUPP)

Explanation Of Carcinogenicity: SEE INGREDIENTS.

Signs And Symptoms Of Overexposure: IRRITATION, PULMONARY INVOLVEMENT, ALLERGIC SKIN RASH, PAIN.

First Aid: INHALATION: REMOVE TO FRESH AIR. SKIN: THOROUGHLY WASH W/SOAP & WATER. EYES: WASH W/WATER FOR 15-20 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Handling and Disposal
=====

Spill Release Procedures: VENTILATE AREA. CLEAN UP USING METHODS WHICH AVOID DUST GENERATION SUCH AS VACUUM, WET DUST MOP/CLEANUP. IF AIRBORNE DUST IS GENERATED, USE AN APPROPRIATE NIOSH APPROVED RESPIRATOR.

Waste Disposal Methods: DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS. MAY BE SOLD AS SCRAP FOR RECLAIM.

Handling And Storage Precautions: MAINTAIN GOOD HOUSEKEEPING PROCEDURES TO PREVENT DUST ACCUMULATION. DON'T USE COOLANT FOR WET CLEAN UP.

Other Precautions: AVOID DUST INHALATION, DIRECT SKIN CONTACT. DON'T SHAKE/CLOTHING, RAGS/OTHER ITEMS TO REMOVE DUST. DUST SHOULD BE REMOVED BY WASHING/VACUUMING W/APPROPRIATE FILTERS. PERIODIC MEDICAL EXAMS ARE RECOMMENDED FOR REGULAR EXPOSURE TO DUST/MIST.

=====
Fire and Explosion Hazard Information
=====

Extinguishing Media: POWDERS, USE DRY SAND, DRY DOLOMITE, ABC TYPE FIRE EXTINGUISHER/FLOOD W/WATER.



Fire Fighting Procedures: POWDER FIRE: CONFINE TO SMALL AREA, USE A RESPIRATOR APPROVED FOR TOXIC DUSTS & FUMES. LARGE: USE SCBA.

Unusual Fire/Explosion Hazard: DUSTS MAY PRESENT A FIRE/EXPLOSION HAZARD UNDER RARE FAVORING CONDITIONS OF PARTICLE SIZE, DISPERSION & STRONG IGNITION SOURCES.

=====
Control Measures
=====

Respiratory Protection: USE AN APPROPRIATE NIOSH APPROVED RESPIRATOR IF AIRBORNE DUST CONCENTRATIONS EXCEED THE PEL/TLV.

Ventilation: LOCAL EXHAUST VENTILATION

Protective Gloves: RECOMMENDED

Eye Protection: SAFETY GLASSES W/SIDE SHIELDS/GOGGLES.

Other Protective Equipment: BARRIER CREAM RECOMMENDED WHEN CONTACT W/DUST/MIST IS LIKELY.

Supplemental Safety and Health: HEALTH HAZARDS CONT'D: SKIN: IRRITATION/ALLERGIC RASH IN COBALT HUPERSENSITIZED INDIVIDUALS. EYES: MILD PAIN/IRRITATION.

=====
Physical/Chemical Properties
=====

Spec Gravity: 5.4 TO 15.5

Solubility in Water: INSOLUBLE

Appearance and Odor: DARK GREY METAL W/NO ODOR.

=====
Reactivity Data
=====

Stability Indicator: YES

Materials To Avoid: STRONG OXIDIZERS, STRONG ACIDS.

Hazardous Decomposition Products: NONE

Hazardous Polymerization Indicator: NO

=====
Toxicological Information
=====

=====
Ecological Information
=====

=====
MSDS Transport Information
=====

=====
Regulatory Information
=====

=====
Other Information
=====

=====
HAZCOM Label
=====



=====
Product ID: CEMENTED CARBIDE
Cage: 5Y454
Company Name: Hartmetall-Werkzeugfabrik Paul Horn GmbH
Street: Unter dem Holz 33-35
City: Tübingen
Zipcode: 72070
Health Emergency Phone:
Label Required IND: Y
Date Of Label Review:
Status Code: C
Label Date:
Origination Code: G

Hazard And Precautions: GRINDING CEMENTED MAY PRODUCE POTENTIALLY HAZARDOUS DUST WHICH CAN BE INHALED, SWALLOWED, COME IN CONTACT W/SKIN & EYES. INHALATION: NOSE & THROAT IRRITATION. POTENTIAL FOR TRANSIENT RESPIRATORY REACTION IN COBALT HYPERSENSITIZED INDIVIDUAL S. PROLONGED USE: PERMANENT/FATAL RESPIRATORY DISEASES. (SEE SUPP) IRRITATION, PULMONARY INVOLVEMENT, ALLERGIC SKIN RASH, PAIN.

=====
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.